

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 17 S., R. 50 E.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T17S R50E

$\frac{1}{4}$ $\frac{S}{S}$ $\frac{6}{7}$

1963

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Continue over nearly level land, through scattering undergrowth.

78.15 Intersect the W. bdy. of the Tp. at the cor. of secs. 1, 6, 7 and 12, monumented with an iron post, $2\frac{1}{2}$ ins. diam., hereinbefore described.

Land, nearly level.

Soil, sandy and gravelly clay loam.

Timber, none; undergrowth, sagebrush and creosote bush.

From the cor. of secs. 5, 6, 7 and 8.

N. $5^{\circ} 15'$ W., bet. secs. 5 and 6.

Over gently rolling land, through medium heavy undergrowth.

36.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T17S R50E

$\frac{1}{4}$
S 6 | S 5

1963

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Continue over gently rolling land, through scattering undergrowth.

71.66 Intersect the Fourth Standard Parallel South.

Point for the closing cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T16S R50E

S 32
S 6 | S 5

T17S R50E

CC

1963

raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, S. of cor. and deposit broken glass around the iron post, 6 ins. below the surface of the ground.