

DEPENDENT RESURVEY OF THE N. BDY. OF T. 16 N., R. 61 E.

CHAINS	
80.61	Point for the cor. of secs. 1 and 2, T. 16 N., R. 61 E., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T17N R61E S 36 S 2 S 1 T16N R61E 1963 from which A pinon, 5 ins. diam., bears S. 0° 15' W., 05 lks. dist., mkd. S 1 BT. No other suitable bearing tree available. Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor. Land, heavily rolling mountainous. Soil, sandy and gravelly clay loam. Timber, pinon and juniper. Undergrowth, sagebrush and mahogany.
	S. 88° 52' E., on the N. bdy. of sec. 1. Over heavily rolling mountainous land, through medium heavy timber and undergrowth; continue ascent; asc. 80 ft. over W. slope.
7.30	Top of Egan Range, bears NW. and SE., begin descent; desc. 540 ft. over an ENE. slope.
39.00	Point for the S. ¼ sec. cor. of sec. 36, T. 17 N., R. 61 E., at a point 40.00 chs. in departure from the SW. cor. of sec. 36. Set an iron post, 36 ins. long, 1 in diam., 20 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd. T17N R61E ¼ S 36 T16N R61E 1963
39.10	Bottom of descent; ravine, drains NE.; asc. 60 ft. over a WSW. slope.
40.30	Point for the N. ¼ sec. cor. of sec. 1, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 36 ins. long, 1 in. diam., 15 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd. T17N R61E ¼ S 1 T16N R61E 1963