

SUBDIVISION OF T. 18 N., R. 47 E.

CHAINS	
	Set an iron post, 28 ins..long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T18N R47E ¼ S 19 S 30 1964 raise a mound of stone, 3 ft. base, 2 ft. high, N. of the iron post. Asc. 70 ft. over an E. slope. 55.00 Base of hills, bears N. and S.; asc. 130 ft. over a steep broken E. slope. 68.90 Small wash, drains NE., 1.00 chains dist.; thence E.; asc. 150 ft. over an E. slope. 74.48 Intersect the East bdy. of T. 18 N., R. 46 E. Point for the closing corner of secs. 19 and 30. Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, and in a mound of stone, 3½ ft. base to top, with brass cap mkd. T18N R46E R47E S 25 S 19 C S 30 C 1964 from which The cor. of secs. 24 and 25, T. 18 N., R. 46 E., heretofore described, bears NORTH, 8.75 chains distance. Land, high rolling. Soil, stony. Undergrowth, sage and bunch grass.
	The point for the ¼ sec. cor. of secs. 30 is at midpoint and on the W. bdy. of the Tp. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T18N R46E R47E ¼ S 30 1964 from which The ¼ sec. cor. of sec. 25, T. 18 N., R. 46 E., heretofore described, bears NORTH, 8.73 chains distance.