

DEPENDENT RESURVEY OF FOURTH STANDARD PARALLEL NORTH, R. 35 E.

CHAINS	At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground with brass cap mkd. SC T21N R35E <u>S 31 S 32</u> 1965 reset the original wooden post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. N. 89° 58' W., along S. bdy. of sec. 31. Over nearly level land, draining NNE., through medium undergrowth. 40.20 Point for the standard ¼ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. SC T21N R35E <u>¼ S 31</u> 1965 raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. 54.50 Bladed dirt road, bears NNE. and SSW. 71.04 The closing cor. of T. 20 N., Rs. 34 and 35 E., hereinafter described. 78.70 Wash, 10 lks. wide, 2 ft. deep, drains N. 80.40 The standard cor. of T. 21 N., Rs. 34 and 35 E., monumented with an iron post, 3 ins. in diam., set, mkd., and witnessed as described in the official records. Land, nearly level. Soil, sandy clay. Undergrowth, sagebrush. DEPENDENT RESURVEY OF THE FOURTH STANDARD PARALLEL NORTH, THROUGH A PORTION OF R. 34 E. Re-establishment of a portion of the survey executed by W. Epler, Deputy Surveyor, in 1865, and independently resurveyed by Walter H. Good, U. S. Surveyor, in 1928. From the standard cor. of sec. 35 and 36, T. 21 N., R. 34 E., monumented with an iron post, 2 ins. in diam., set, mkd., and witnessed as described in the official records. N. 89° 59' W., along the S. bdy. of sec. 35.
--------	--