

DEPENDENT RESURVEY, T. 17 S., R. 51 E.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T17S R51E

$\frac{1}{4}$
S 2 | S 1

1966

no accessories available.

73.63

Intersect the Fourth Standard Parallel South.

Point for the closing cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T16S R51E

S 36
S 2 | S 1

CC

T17S R51E

1966

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the standard cor. of secs. 35 and 36, T. 16 S., R. 51 E., bears S. $89^{\circ} 48'$ W., 10.53 chs. dist.

Land, level.

Soil, sandy clay.

Vegetation, mesquite and creosote.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 1, on the Fourth Standard Parallel and at midpoint on the N. bdy. of sec. 1.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 1
T17S R51E

1966

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor. the standard $\frac{1}{4}$ sec. cor. of sec. 36, T. 16 S., R. 51 E., bears S. $89^{\circ} 48'$ W., 9.57 chs. dist.

From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the Tp.