

DEPENDENT RESURVEY, T. 17 S., R. 51 E.

CHAINS

74.12 set a wooden post, 4 ins. square, 4 ft. long, 24 ins. in the ground alongside the iron post.

Intersect the Fourth Standard Parallel South.

Point for the closing cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T16S R51E
 S 35
 S 3 | S 2
 cc
 T17S R51E

1966

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the standard cor. of secs. 34 and 35, T. 16 S., R. 51 E., bears S. $89^{\circ} 48'$ W., 10.56 chs. dist.

Land, level.

Soil, sandy clay.

Vegetation, shadscale and creosote.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 2, on the Fourth Standard Parallel South and at midpoint on the N. bdy. of sec. 2.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 2
 T17S R51E

1966

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor. the standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 16 S., R. 51 E., bears S. $89^{\circ} 48'$ W., 10.545 chs. dist.

From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the Tp.

N. $1^{\circ} 00'$ W., bet. secs. 33 and 34.

Over mountainous land; asc. 130 ft. over SW. slope.

3.00

Spur, slopes NW.; desc. 440 ft. over N. slope.