

## DEPENDENT RESURVEY, T. 17 S., R. 51 E.

## CHAINS

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T17S R51E

$\frac{1}{2}$   
S 4 | S 3

1966

set a wooden post, 4 ins. square, 4 ft. long, 24 ins. in the ground alongside the iron post.

74.46

Intersect the Fourth Standard Parallel South.

Point for the closing cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T16S R51E

S 34

S 4 | S 3

cc

T17S R51E

1966

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor. the standard cor. of secs. 33 and 34, T. 16 S., R. 51 E., bears S.  $89^{\circ} 48' W.$ , 10.79 chs. dist.

Land, level.

Soil, sandy clay.

Vegetation, creosote and shadscale.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 3, on the Fourth Standard Parallel South and at midpoint on the N. bdy. of sec. 3.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$  S 3

T17S R51E

1966.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor. the standard  $\frac{1}{4}$  sec. cor. of sec. 34, T. 16 S., R. 51 E., bears S.  $89^{\circ} 48' W.$ , 10.675 chs. dist.

From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the Tp.

N.  $2^{\circ} 21' W.$ , bet. secs. 32 and 33.