

DEPENDENT RESURVEY, T. 17 S., R. 51 E.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T17S R51E

S $5\frac{1}{2}$ S 4

1966

set a wooden post, 4 ins. square, 4 ft. long, 24 ins. in the ground alongside the iron post.

74.88

Intersect the Fourth Standard Parallel South.

Point for the closing cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T16S R51E

S 33
S 5 S 4
cc

T17S R51E

1966

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor. the standard cor. of secs. 32 and 33, T. 16 S., R. 51 E., bears S. $89^{\circ} 48'$ W., 10.92 chs. dist.

Land, level.

Soil, sandy clay.

Vegetation, creosote and shadscale.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 4, on the Fourth Standard Parallel South and at midpoint on the N. bdy. of sec. 4.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 4
T17S R51E

1966

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor. the standard $\frac{1}{4}$ sec. cor. of sec. 33, T. 16 S., R. 51 E., bears S. $89^{\circ} 48'$ W., 10.855 chs. dist.