

DEPENDENT RESURVEY, T. 17 S., R. 51 E.

CHAINS

no accessories available.

78.23

The cor. of secs. 1, 6, 7 and 12 on the W. bdy, of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.

Land, level.

Soil, sandy clay.

Vegetation, creosote and shadscale.

From the cor. of secs. 5, 6, 7 and 8.

N. $1^{\circ} 13'$ W., bet. secs. 5 and 6.

Over level land, through scattered vegetation.

38.80

Power line, bears N. $66\frac{3}{4}^{\circ}$ W. and S. $66\frac{3}{4}^{\circ}$ E.

38.93

Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T17S R51E

$\frac{1}{4}$
S 6 | S 5

1966

set a wooden post, 4 ins. square, 4 ft. long, 24 ins. in the ground alongside the iron post.

75.19

Intersect the Fourth Standard Parallel South.

Point for the closing cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T16S R51E

S 32
S 6 | S 5
cc

T17S R51E

1966

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor. the standard cor. of secs. 31 and 32, T. 16 S., R. 51 E., bears S. $89^{\circ} 48'$ W., 10.86 chs. dist.