

DEPENDENT RESURVEY OF THE WEST BDY., T. 26 N., R. 64 E.

CHAINS	
80.98	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to cap, 6 ft. base, with brass cap mkd. T26N R63E R64E S 1 S 6 S 12 S 7 1966 Land, mountainous. Soil, rocky and light gravel. Undergrowth, native grasses. Timber, juniper.
	N. 0° 40' W., bet. secs. 1 and 6. Over mountainous land, through medium timber; ascend 500 ft. over a SSE. slope.
23.00	Spur, slopes E.; descend 150 ft. over an E. slope.
40.49	Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to cap, 6 ft. base, with brass cap mkd. T26N R63E R64E S 1 S 6 S 12 S 7 1966
41.50	Head of draw, drains irregularly E.; ascend 200 ft. over a SE. slope.
53.50	Spur, slopes NE.; descend 190 ft. over a NW. slope.
58.30	Draw, drains E.; ascend 230 ft. over a SE. slope.
65.00	Spur, slopes ENE.; descend 90 ft. over a N. slope.
70.00	Draw, drains ENE.; ascend 160 ft. over an E. slope.
80.98	The cor. of Tps. 26 and 27 N., Rs. 63 and 64 E., monumented with a limestone, 18x16x10 ins., plainly mkd. 6 notches on all four edges and firmly set in a mound of stone. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.