

DEPENDENT RESURVEY OF THE WEST BDY., T. 26 N., R. 64 E.

CHAINS

T27N
R63E R64E
S 36 | S 31
S 1 | S 6
T26N

1966

from which

A juniper, 6 ins. diam., bears N. $53\frac{1}{2}^{\circ}$ E.,
17 lks. dist., mkd. S 31 BT.

A pinon pine, 10 ins. diam., bears S. $37\frac{1}{2}^{\circ}$ E.,
35 lks. dist., mkd. T26N R64E S 6 BT.

A pinon pine, 7 ins. diam., bears S. $21\frac{1}{2}^{\circ}$ W.,
45 lks. dist., mkd. S 1 BT.

A pinon pine, 10 ins. diam., bears N. $3\frac{1}{2}^{\circ}$ W.,
15 lks. dist., mkd. T27N R63E S 36 BT.

Bury the original corner stone alongside the iron
post.

Land, mountainous.

Soil, light gravel and rocky.

Undergrowth, native grasses.

Timber, juniper and pinon pine.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES OF
T. 26 N., R. 64 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
Preble and Thorburn, U. S. Deputy Surveyors,
in 1882

From the standard cor. of secs. 35 and 36, on the S. bdy.
of the Tp.

N. $0^{\circ} 12'$ E., bet. secs. 35 and 36.

Over nearly level lake bed, through dense undergrowth.

40.34 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at pro-
portionate distance; there is no remaining evidence of
the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T26N R64E
 $\frac{1}{4}$
S 35 | S 36

1966

raise a mound of stone, 3 ft. base, 3 ft. high, W. of
cor.