

DEPENDENT RESURVEY OF T. 26 N., R. 64 E.

CHAINS

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., described in the field notes of the dependent resurvey of the W. bdy. of T. 26 N., R. 65 E., executed concurrently under this same group.

S. $89^{\circ} 51'$ W., bet. secs. 13 and 24.

Over nearly level lake bed, through medium undergrowth.

40.20

Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T26N R64E

$\frac{1}{4}$ S 13
S 24

1966

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

80.40

The cor. of secs. 13, 14, 23 and 24.

Land, nearly level.

Soil, clay and sandy loam.

Undergrowth, greasewood.

N. $0^{\circ} 07'$ W., bet. secs. 13 and 14.

Over nearly level lake bed, through medium undergrowth.

40.34

Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T26N R64E

$\frac{1}{4}$
S 14 | S 13

1966

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

50.50

Leave Goshute Lake bed (dry), edge bears NE. and SW.

80.68

Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.