

DEPENDENT RESURVEY OF T. 26 N., R. 64 E.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T26N R64E

$\frac{1}{4}$
S 3 | S 2

1966

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

55.50 Fence, bears NW. and SE.

80.59 The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., described in the field notes of the dependent resurvey of the S. bdy. of T. 27 N., R. 64 E., executed concurrently under this same group.

Land, nearly level.

Soil, sandy loam.

Undergrowth, native grasses and sagebrush.

From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp.

N. $0^{\circ} 59'$ E., bet. secs. 33 and 34.

Over nearly level meadow land, with numerous small springs, draining SE.

39.95 The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, monumented with a wooden post, 18 ins. long, 4x4 ins. squared, dimly mkd. $\frac{1}{4}$ and loosely set in a mound of earth.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T26N R64E

$\frac{1}{4}$
S 33 | S. 34

1966

bury the original wooden post alongside iron post and set a cedar post, 6 ft. long, 8 ins. diam., 30 ins. in the ground.

N. $0^{\circ} 59'$ E., beginning new measurement.

39.95 The cor. of secs. 27, 28, 33 and 34, monumented with a wooden post, 18 ins. long, 4 ins. diam., dimly scribed and loosely set in a mound of earth.

At the corner point