

DEPENDENT RESURVEY OF THE WEST BDY. OF T. 27 N., R. 64 E.

CHAINS

80.24

Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T27N
R63E R64E
S 1 | S 6
S 12 | S 7

1966

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, gently rolling.

Soil, sandy clay and light gravel.

Undergrowth, sagebrush and native grasses.

40.12

N. $0^{\circ} 12'$ E., bet. secs. 1 and 6.

Over gently rolling land, through medium undergrowth.

Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T27N
R63E R64E
 $\frac{1}{4}$
S 1 | S 6

1966

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

From this corner, Willow Springs, bears N. $49-3/4^{\circ}$ E., 19.60 chs. dist.

80.24

The cor. of Tps. 27 and 28 N., Rs. 63 and 64 E., monumented with a badly decayed wooden post and a limestone, 12x8x8 ins., mkd. 6 notches on the N., S., E. and W. faces.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.