

DEPENDENT RESURVEY OF A
PORTION OF THE FIFTH STANDARD PARALLEL NORTH,
THROUGH RANGE 65 EAST

CHAINS	DEPENDENT RESURVEY OF A PORTION OF THE FIFTH STANDARD PARALLEL NORTH, THROUGH RANGE 65 EAST, MOUNT DIABLO MERIDIAN, NEVADA Reestablishment of the Survey Executed by Preble and Thorburn, U. S. Deputy Surveyors, in 1881; Resurveyed by W. A. Pray, U. S. Deputy Surveyor, in 1909; and Resurveyed by A. Nelson, Cadastral Engineer, in 1927. Beginning at the standard cor. of secs. 31 and 32, monumented with a limestone, 8x8x3 ins. above ground, firmly set and plainly mkd. 1 notch on the W. edge, 5 notches on the E. edge and SC on the N. face. This appears to be the 1909 remonumentation. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. SC T26N R65E S 31 S 32 1966 bury the corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. S. 89° 57' W., along the south bdy. of sec. 31. Over nearly level land, through medium undergrowth. 0.94 The closing cor. of secs. 1 and 6, T. 26 N., Rs. 64 and 65 E., monumented with a flint stone, 12x8x4 ins., mkd. CC 25N on the north face and 6 notches on the south and west faces and firmly set in a mound of earth. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T26N R65E S 31 S 1 S 6 R64E R65E T25N CC 1966 bury the corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor. Reestablishment of the Survey Executed by Preble and Thorburn, U. S. Deputy Surveyors, in 1881 and Resurveyed by W. A. Pray, U. S. Deputy Surveyor, in 1909. Continue bearing and distance. 39.96 Point for the standard ¼ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the corner.
--------	---