INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 69 E., MDM, NEVADA

CHAINS	
50.60	Spur, slopes ENE.; desc. 70 ft. over N. slope.
55.80	Draw, drains E.; asc. 90 ft. over S. slope.
59.70	Spur, slopes E.; desc. 60 ft. over N. slope.
64.20	Draw, drains E.; asc. 50 ft. over S. slope.
71.00	Spur, slopes ENE.; desc. 40 ft. over S. slope.
74.40	Draw, drains E.; asc. slightly over S. slope.
82.20	Draw, drains E.; asc. gradually over S. slope.
82.81	Intersect the Sixth Standard Parallel North.
	Point for the closing cor. of secs. 3 and 4.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T31N R69E
S 33
S 4 | S 3
C | C
T30N R69E

1971

from this corner

The standard ¼ sec. cor. of sec. 33, T. 31 N., R. 69 E., monumented with an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North, through R. 69 E., resurveyed concurrently under this same group, bears S. 88° 29' E., 12.28 chs. dist.

Land, rolling.
Soil, sandy clay and rocky.
Timber, none.
Undergrowth, sagebrush, greasewood and bunchgrass.

The point for the N. ¼ sec. cor. of sec. 3 is on the Sixth Standard Parallel North and at midpoint in departure on the N. bdy. of sec. 3.

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to cap, with brass cap mkd.

¼ S 3
T30N R69E

1971