

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 32 N., R. 18 E., MDM, NEVADA

| CHAINS |                                                                                                                                                                                                          |  |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|        | N. 89° 55' W., bet. secs. 18 and 19.                                                                                                                                                                     |  |
|        | Over mountainous land, covered with sagebrush.                                                                                                                                                           |  |
| 3.00   | Ridge, bears SW. and NE.; desc. 370 ft. over NW. slope.                                                                                                                                                  |  |
| 40.14  | The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, monumented with a mound of stone, firmly embedded in the ground; this is accepted as the best available evidence of the position of the original corner. |  |
|        | At the corner point                                                                                                                                                                                      |  |
|        | Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.                                           |  |
|        | <div style="text-align: center;"> T32N R18E<br/> <math>\frac{1}{4}</math> <math>\frac{S\ 18}{S\ 19}</math> </div>                                                                                        |  |
|        | 1972                                                                                                                                                                                                     |  |
|        | set a steel fence post, 6 ft. long, alongside the iron post.                                                                                                                                             |  |
|        | <hr/>                                                                                                                                                                                                    |  |
|        | N. 89° 56' W., beginning new measurement.                                                                                                                                                                |  |
|        | Over mountainous land; desc. 30 ft. over NW. slope.                                                                                                                                                      |  |
| 16.00  | Draw, drains N.; asc. 120 ft. over NE. slope.                                                                                                                                                            |  |
| 36.50  | Spur, slopes N.; desc. 10 ft. over NW. slope.                                                                                                                                                            |  |
| 39.02  | The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with a scoria stone, 20x15x8 ins., firmly set in a mound of stone, mkd. with 3 notches on the S. and N. edges.                |  |
|        | At the corner point                                                                                                                                                                                      |  |
|        | Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.                                            |  |
|        | <div style="text-align: center;"> T32N<br/> R17E R18E<br/> <math>\frac{S\ 13}{S\ 24}</math> <math>\frac{S\ 18}{S\ 19}</math> </div>                                                                      |  |
|        | 1972                                                                                                                                                                                                     |  |
|        | deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post.                                                                                                        |  |
|        | <hr/>                                                                                                                                                                                                    |  |