

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 33 N., R. 18 E., MDM, NEVADA

CHAINS	
	bury the original corner stone alongside the iron post. This corner is located on a ridge, bearing NNW. and SSE. N. 0° 08' E., beginning new measurement. Ascend slightly over ESE. slope of ridge.
35.50	Ridge, bears NE. and SW.; asc. slightly along W. slope of ridge.
40.16	The cor. of secs. 25, 26, 35 and 36, monumented with a scoria stone, 26x18x14 ins., firmly set in a mound of stone, mkd. with 1 groove on the S. and E. faces. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd. T33N R18E S 26 S 25 S 35 S 36 1973 bury the original corner stone alongside the iron post. From the cor. of secs. 25 and 36, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, 8 ft. base to top, with brass cap mkd. T33N S 25 T33N S 36 R19E R18E S 31 1927 S. 89° 07' W., bet. secs. 25 and 36. Over mountainous land, covered with sagebrush and bunch-grass; desc. 210 ft. over SW. slope.
21.50	Draw, drains SE.; asc. 300 ft. over NE. slope.
40.76	The ¼ sec. cor. of secs. 25 and 36, monumented with a basalt stone, 10x10x4 ins., firmly set in a mound of stone, mkd. ¼ on the N. face. At the corner point