

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 33 N., R. 18 E., MDM, NEVADA

CHAINS	
40.21	The cor. of secs. 23, 24, 25 and 26, monumented with a scoria stone, 26x12x12 ins., firmly set in a mound of stone, mkd. with 1 groove on the E. face and 2 grooves on the S. face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd. T33N R18E S 23 S 24 S 26 S 25 1973 bury the original corner stone alongside the iron post. From the cor. of secs. 24 and 25, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, 4 ft. base to top, with brass cap mkd. T33N S 24 T33N S 25 R19E R18E S 30 1927 From this corner, Parsnip Spring, 50 lks. diam., bears S. 7 3/4° E., 6.30 lks. dist., course NE. S. 88° 20' W., bet. secs. 24 and 25. Over mountainous land, covered with sagebrush and bunch-grass; asc. 280 ft. over broken NE. slope to the ¼ sec. cor.
9.40	Trail road, bears ENE. and WSW.
17.10	Same trail road, bears SSE. and NNW.
42.36	The ¼ sec. cor. of secs. 24 and 25, monumented with a basalt stone, 18x16x10 ins., firmly set in a mound of stone, mkd. ¼ on the N. face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd. T33N R18E S 24 ¼ S 25 1973 bury the original corner stone alongside the iron post.