

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 33 N., R. 18 E., MDM, NEVADA

CHAINS	
	T33N R18E $\frac{S \ 2}{S \ 11} \frac{S \ 1}{S \ 12}$ 1973 bury the original corner stone alongside the iron post. From the cor. of secs. 1 and 12, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set and exposed 12 ins. above the ground, with a mound of stone, 3 ft. base, 2 ft. high, W. of cor., with brass cap mkd. T33N T33N R18E R19E $\frac{S \ 1}{S \ 12} S \ 7$ 1927 S. 89° 54' W., bet. secs. 1 and 12. Over rolling land, covered with sagebrush and bunchgrass. 40.40 Wash, 10 lks. wide, 1 ft. deep, drains NNE. 40.61 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd. T33N R18E $\frac{S \ 1}{S \ 12}$ 1973 Ascend 170 ft. over NE. slope. 59.00 Rim rock, bears N. and S. 81.22 The cor. of secs. 1, 2, 11 and 12. N. 0° 21' E., bet. secs. 1 and 2. Over rolling land, covered with sagebrush and bunchgrass. 16.60 Rim rock, bears SE. and WNW.; desc. 120 ft. over NE. slope. 23.80 Trail road, bears ESE. and WNW.; desc. 70 ft. over NE. slope. 36.00 Wash, 30 lks. wide, 2 ft. deep, drains ESE.; asc. slightly over SE. slope.