DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
OF T. 36 N., R. 64 E., MDM, NEVADA

CHAINS	
39.66	Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T36N R64E ¼ S 3|S 2 1976 raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.
79.86	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an aluminum post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the resurvey of T. 37 N., R. 64 E., executed under this same group.
	From the standard corner of secs. 33 and 34, on the S. bdy. of the Tp. N. 0° 05' W., bet. secs. 33 and 34. Over near level land, through tule ponds.
40.08	Point for the ¼ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T36N R64E ¼ S 33|S 34 1976 set a steel fence post, 5½ ft. long, 2 ft. in the ground, alongside aluminum post.
80.16	Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T36N R64E S 28|S 27 S 33|S 34 1976 set a steel fence post, 5½ ft. long, 2 ft. in the ground, alongside aluminum post.