10

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF
T. 38 N., R. 57 E., MDM, NEVADA

CHAINS	
33.25	The closing corner of secs. 6 and 7, T. 38 N., R. 58 E., monumented with a granite stone, 14 x 8 x 8 ins., mkd. with 5 grooves on the S. face, 1 groove on the N. face and CC on the E. face, firmly set and exposed 10 ins. above ground, with a steel fence post firmly set alongside. At the corner point Set an iron post, 28 ins. long, 22 ins. in the ground, with brass cap mkd. T38N R57E R58E S 12 | S 6 C / S 7 C 1978 bury the original cornerstone and reset the steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.
40.45	The cor. of secs. 1 and 12, monumented with a willow post, 1 in. square, 15 ins. long, loosely set in a mound of earth, with a steel fence post firmly set alongside. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T38N R57E R58E S 1 | S 6 / S 12 | 1978 bury the original wooden post and reset the steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.
	N. 2° 05' E., along the E. bdy. of sec. 1. Over rolling land, through sagebrush; along W. slope.
30.00	Bladed road, bears WNW. and SW., on curve.
32.68	Point for the W. ¼ sec. cor. of sec. 6, T. 38 N., R. 58 E., at proportionate distance.

U.S. Government Printing Office-1978-778-206/433