

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 38 N., R. 64 E., MDM, NEVADA

CHAINS		
	N. 1° 27' W., bet. secs. 2 and 3. Over rolling land, through medium sagebrush and bunchgrass.	
40.46	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T38N R64E $\frac{1}{4}$ S 31S 2 1978 set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.	
80.34	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp. From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 64 E., executed under Group No. 533. N. 0° 52' W., bet. secs. 33 and 34. Over rolling land, through medium sagebrush and bunchgrass.	
39.31	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T38N R64E $\frac{1}{4}$ S 33S 34 1978 set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.	
78.62	Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.	