

DEPENDENT RESURVEY OF
THE FOURTH STANDARD PARALLEL NORTH,
THROUGH R. 43 E., MDM, NEVADA

CHAINS	
81.00	The original standard cor. of secs. 31 and 32 monumented with a wooden post, 15 ins. long, 3 ins. square, firmly set with a steel fence post, alongside with illegible scribe marks visible. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. SC T21N R43E <u>S 31 S 32</u> 1978 reset the wooden post and steel fence post, 5 ft. long, 2 ft. in the ground, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. From this corner, U.S.C. & G.S. triangulation station "SKULL" set in a concrete cylinder, mkd. SKULL 1954, exposed 6 ins. above ground, bears N. $58^{\circ} 50'$ E., 45.98 chs. dist.
	S. $89^{\circ} 56'$ W., along the S. bdy. of sec. 31.
	Over rolling land, through scattered sagebrush, greasewood and shadscale.
5.37	The closing cor. of secs. 5 and 6, monumented with an iron post $2\frac{1}{2}$ ins. diam., hereinafter described.
26.00	Wash, 20 lks. wide, 3 ft. deep, drains WSW.
40.43	The original standard $\frac{1}{4}$ sec. cor. of sec. 31, monumented with a shaved wooden post, 36 ins. long, 3 ins. diam., firmly set and exposed 24 ins. above the ground with illegible scribe marks visible, alongside a steel fence post. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. SC T21N R43E <u>$\frac{1}{4}$ S 31</u> 1978 reset the wooden post and steel fence post, 5 ft. long, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. _____ N. $89^{\circ} 54'$ W., beginning new measurement. Over nearly level land.