

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 20 N., R. 43 E., MDM, NEVADA

CHAINS	The point for the N. $\frac{1}{4}$ sec. cor. of sec. 6 is on the Fourth Standard Parallel North and on the S. bdy. of sec. 31, T. 21 N., R. 43 E., and at proportionate distance in departure on the N. bdy. of sec. 6. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\frac{1}{4}$ S 6 T20N R43E 1978 raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor. From this corner, the standard $\frac{1}{4}$ sec. cor. of sec. 31, hereinbefore described, bears S. $89^{\circ} 54'$ E., 2.10 chs. dist. SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T . 20 N., R. 43 E., MOUNT DIABLO MERIDIAN, NEVADA From the cor. of secs. 8, 9, 16 and 17, monumented with an iron post $2\frac{1}{2}$ ins. diam., hereinbefore described. EAST, on a Sectional Correction Line bet. secs. 9 and 16, on transit line describing the tangent. Over gently rolling land, through scattered sagebrush and shadscale. 40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 9 and 16, North 0.2 lk. from the tangent. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T20N R43E $\frac{1}{4}$ S 9 S 16 1979 set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the iron post. 44.00 Italian Creek, 20 lks. wide, 1 ft. deep, course WNW. 80.00 Point for the cor. of secs. 9, 10, 15 and 16, North 0.8 lk. from the tangent.
--------	--