

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 43 E., MDM, NEVADA

CHAINS	
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. and set a steel fence post, 5 ft. long, 24 ins. in the ground, alongside the iron post.
81.52	Intersect the Fourth Standard Parallel North. Point for the closing cor. of secs. 2 and 3. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T21N R43E S 34 S 31S 2 T20N R43E CC 1979 raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor. and set a steel fence post, 5 ft. long, 24 ins. in the ground, alongside the iron post. From this corner, the standard cor. of secs. 34 and 35, T. 21 N., R. 43 E., monumented with an iron post, 2½ ins. diam., hereinbefore described, bears S. 89° 56' E., 8.45 chs. dist. Land, rolling. Soil, sandy clay. Undergrowth, sagebrush and shadscale.
	Point for the N. ¼ sec. cor. of sec. 2, at 40.00 chs. in departure from the closing cor. of secs. 2 and 3, and on the S. bdy. of sec. 35, T. 21 N., R. 43 E. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. ¼ S 2 T20N R43E 1979 raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor. and set a steel fence post, 5 ft. long, 24 ins. in the ground, alongside the iron post. From this corner, the standard ¼ sec. cor. of sec. 35, T. 21 N., R. 43 E., monumented with an iron post, 2½ ins. diam., hereinbefore described, bears N. 89° 55' E., 8.80 chs. dist.
	From the cor. of secs. 9 10, 15 and 16. S. 0° 01' E., bet. secs. 15 and 16. Over rolling land, through sagebrush and shadscale.