

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

T. 20 N., R. 43 E., MDM, NEVADA

CHAINS

40.01

Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.

Set an iron post, 28 ins. long. $2\frac{1}{2}$ ins. diam., 18 ins. in the ground and in a collar of stone, with brass cap mkd.

T20N R43E
 $\frac{1}{4}$ S 3
 S 10

1979

set a steel fence post, 5 ft. long, 18 ins. in the ground, alongside the iron post.

80.02

The cor. of secs. 3, 4, 9 and 10.

Land, rolling.
 Soil, sandy clay.
 Undergrowth, sagebrush.

N. $0^{\circ} 01'$ W., bet. secs. 3 and 4.

Over rolling land, through sagebrush.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T20N R43E
 $\frac{1}{4}$
 S 4 | S 3

1979

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. and set a steel fence post, 5 ft. long, 24 ins. in the ground, alongside the iron post.

61.00

Wash, 10 lks. wide, 1 ft. deep, drains WSW.

81.59

Intersect the Fourth Standard Parallel North.

Point for the closing cor. of secs. 3 and 4.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T21N R43E
 S 33
 S 4 | S 3
 T20N R43E
 CC

1979