

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 43 E., MDM, NEVADA

CHAINS	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T20N R43E ¼. S 5½S 4 1979 set a steel fence post, 5 ft. long, 24 ins. in the ground, alongside the iron post. 81.80 Intersect the Fourth Standard Parallel North. Point for the closing cor. of secs. 4 and 5. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T21N R43E S 32 S. 5½S 4 T20N R43E CC 1979 raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor. and set a steel fence post, 5 ft. long, 24 ins. in the ground, alongside the iron post. From this corner, the standard cor. of secs. 32 and 33, monumented with an iron post, 2½ ins. diam., hereinbefore described, bears N. 89° 57' E., 6.70 chs. dist. Land, rolling. Soil, sandy clay. Undergrowth, sagebrush. Point for the N. ¼. sec. cor. of sec. 4, on the S. bdy. of sec. 33, T. 21 N., R. 43 E., and at midpoint bet. closing corners. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. ¼. S 4 T20N R43E 1979 raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor. and set a steel fence post, 5 ft. long, 24 ins. in the ground, alongside the iron post.
--------	--