

221

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 7 N., R. 26 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 7 N., R. 26 E., MDM, NEVADA

Reestablishment of the Survey Executed by
R. A. Chase, U. S. Deputy Surveyor,
in 1870.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 8 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 7 N., R. 26 E., executed under Group No. 458.

S. $89^{\circ} 58'$ W., bet. secs. 2 and 35.

Over mountainous land, covered with sagebrush native grass and scattered juniper.

39.47 The $\frac{1}{4}$ sec. cor. of secs. 2 and 35, monumented with a trap stone, 16x10x10 ins., firmly set 6 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, with mound of stone N.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

	T7N	R26E
	S	35
$\frac{1}{4}$	S	2
	T6N	

1980

Deposit the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

S. $89^{\circ} 56'$ W., beginning new measurement.

Over mountainous land.

35.00 Ridge, bears NE. and SW.

40.40 The cor. of secs. 2, 3, 34 and 35, monumented with a trap stone, 26x16x14 ins., firmly set in a mound of stone, mkd. with 2 notches on the E. edge and 4 notches on the W. edge.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.