

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 7 N., R. 26 E., MDM, NEVADA

CHAINS	T7N R26E S 34 S 35 S 3 S 2 T6N 1980 Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post. DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY, T. 7 N., R. 26 E., MDM, NEVADA Reestablishment of the Survey Executed by R. A. Chase, U. S. Deputy Surveyor, in 1870. From the cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with a porphyry stone, 10x10x8 ins., firmly set in a mound of stone, mkd. with 1 notch on the S. edge and 5 notches on the N. edge. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground to solid rock and in a collar of stone, 3 ft. base to top, with brass cap mkd. T7N R25E R26E S 25 S 30 S 36 S 31 1980 Deposit the original corner stone and set a steel fence post, 5½ ft. long, alongside the iron post. N. 0° 08' W., bet. secs. 25 and 30. Over rolling land, covered with sagebrush and native grass. 0.10 Fence, bears E. and W. 20.00 Enter meadow land, edge bears E. and W. 24.30 Fence, bears E. and W. 27.00 Right bank, East Walker River, bears SE. and NW., course SE. 28.50 Left bank, East Walker River, bears SE. and NW. 40.46 Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.
--------	--