

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 7 N., R. 26 E., MDM, NEVADA

CHAINS

80.92

The cor. of secs. 13, 18, 19 and 24, monumented with a trachyte stone, 18x10x8 ins., firmly set in a mound of stone, mkd. with 3 notches on the N. and S. edges.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T7N
R25E R26E
S 13 | S 18
S 24 | S 19

1980

Deposit the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 7 N., R. 26 E., MDM, NEVADA

Reestablishment of the Survey Executed by
R. A. Chase, U. S. Deputy Surveyor, in 1870 and
the Resurvey Executed by D. E. Beck, Cadastral Surveyor
and W. L. Jepson, Surveying Technician, in 1969.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy.
of the Tp.

N. $0^{\circ} 28'$ W., bet. secs. 35 and 36.

Over rolling land, covered with sagebrush and scattered juniper.

40.10

The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 7 N., R. 26 E., executed under Group No. 458.

From this cor., a U.S.G.S. Bench Mark, monumented with an iron post, 4 ins. diam., firmly set showing 8 ins. above the ground, with brass cap mkd. 5631, bears N. $42^{\circ} 52'$ W., 15.35 chs. dist.

N. $1^{\circ} 07'$ E., beginning new measurement.

Over rolling land.

9.00

Graded road, bears ESE. and WNW.

12.70

Fence, bears E. and W.