

241

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 7 N., R. 26 E., MDM, NEVADA

CHAINS	
	$E \ 1/16 \ \frac{S \ 18}{S \ 19}$
	1980
	Set a steel fence post, 5½ ft. long, alongside the iron post.
41.20	The ¼ sec. cor. of secs. 18 and 19, monumented with a basalt stone, 20x14x10 ins., firmly set in a mound of stone, mkd. ¼ on the N. face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	$T7N \ R26E$ $\frac{1}{4} \ \frac{S \ 18}{S \ 19}$
	1980
	Deposit the original cornerstone alongside the iron post.
	S. 89° 30' W., beginning new measurement.
	Over rolling land, covered with sagebrush and scattered juniper.
41.34	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp.
	SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 7 N., R. 26 E., MDM, NEVADA
	From the ¼ sec. cor. of secs. 23 and 26.
	N. 89° 49' E., bet. secs. 23 and 26.
	Over mountainous land, covered with sagebrush and native grass.
40.23	The cor. of secs. 25 and 26.
	Land; mountainous
	Soil; rocky
	Undergrowth; sagebrush and native grass.
	From the cor. of secs. 17, 18, 19 and 20.
	EAST, on a Sectional Correction Line on the S. bdy. of sec. 17, on a transit line describing the tangent.