

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 21 N., R. 42 E., MDM, NEVADA

CHAINS	
	T22N R42E S 6 S 5 T21N R42E 1981
40.23	N. 88° 05' W., along the N. bdy. of sec. 6. Over rolling land, covered with sagebrush and native grass. The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented with a granite stone, 12x6x6 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on the W. face. Hereafter, this cor. will refer to sec. 6 only. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T22N R42E $\frac{1}{4}$ S 6 T21N R42E 1981 Reset the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
39.88	N. 89° 41' W., beginning new measurement. Over rolling land. The cor. of Tps. 21 and 22 N., Rs. 41 and 42 E., monumented with a granite stone, 30x14x14 ins., firmly set in a mound of stone, mkd. with 6 notches on the N., S., E. and W. edges. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T22N R41E R42E S 36 S 31 S 1 S 6 T21N 1981 Reset the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high S. of cor.