

362

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 66 E., MDM, NEVADA

CHAINS	
42.45	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp. S. 89° 22' W., bet. secs. 1 and 12. Over rolling land, through scattered sagebrush and juniper. Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T40N R66E $\frac{1}{4}$ S 1 S 12 1980 Set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the aluminum post.
84.90	The cor. of secs. 1, 2, 11 and 12. N. 3° 24' W., bet. secs. 1 and 2. Over rolling land, through scattered sagebrush and juniper.
29.14	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T40N R66E $\frac{1}{4}$ S 2 S 1 1980 Set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the aluminum post.
44.88	The original closing cor. of secs. 1 and 2, monumented with a wooden post, 30 ins. long, 3 ins. square, with illegible scribe marks visible, firmly set 10 ins. in the ground. At the corner point Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.