

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 40 N., R. 69 E., MDM, NEVADA

CHAINS		
	T40N R69E $\frac{S}{\frac{1}{4}} \frac{6}{7}$ 1986 Set a steel fence post, 5½ ft. long, alongside the stainless steel post. 75.72 The cor. of secs. 6 and 7, on the W. bdy. of the Tp.	
	From the cor. of secs. 5, 6, 7 and 8. N. 0° 15' E., bet. secs. 5 and 6. Over rolling land, covered with scattered sagebrush, greasewood, rabbitbrush and native grass.	
11.50	Trail road, bears NW. and SE.	
27.40	Wash, 20 lks. wide, 2 ft. deep, drains ESE.	
40.14	The ¼ sec. cor. of secs. 6 and 7, monumented with a limestone, 16x7x5 ins., firmly set in a mound of stone, plainly mkd. ¼ on W. face (Record: wooden post and no original bearing trees found), with a steel fence post, 5½ ft. long, firmly set alongside. At the corner point Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T40N R69E $\frac{S}{\frac{1}{4}} 6 S 5$ 1986 Deposit the marked stone and reset the steel fence post alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 1½ ft. high, W. of cor.	
	N. 0° 27' E., beginning new measurement. Over rolling land.	
34.50	Intersect the Eighth Standard Parallel North. Point for the closing cor. of secs. 5 and 6. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	