

407

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL
NORTH, THROUGH RANGE 70 EAST, MDM, NEVADA

CHAINS	
	From this corner, a U.S.G.S. triangulation station "BM GWM 19" monumented with a standard brass tablet, set in the top of a 6 in. square concrete monument, exposed 8 ins. above the ground, stamped" 5057 FEET GWM 19 1939," bears N. 24° 26' E., 125.78 chs. dist. N. 89° 33' E., along the S. bdy. of sec. 32. Over gently rolling land, through scattered sagebrush and native grass.
22.58	The closing cor. of secs. 4 and 5, T. 40 N., R. 70 E., hereinafter described.
40.88	Point for the standard $\frac{1}{4}$ sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. SC T41N R70E <u>$\frac{1}{4}$ S 32</u> 1987 Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
45.40	Wash, 20 lks. wide, 4 ft. deep, drains S.
63.46	The N $\frac{1}{4}$ sec. cor. of sec. 4, T. 40 N., R. 70 E., hereinafter described.
81.76	Point for the standard cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. SC T41N R70E <u>S 32 S 33</u> 1987 Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. N. 89° 33' E., along the S. bdy. of bdy. of sec. 33. Over gently rolling land, through scattered sagebrush and native grass.
28.20	Trail road, bears N. and S.
28.35	The original standard closing cor. of T. 41 N., R. 70 E., monumented with a wooden post, 2 ins. square, 20 ins. long, firmly set in a mound of earth, in a fence bearing N. and S., with illegible scribe marks visible. Add the marks AM and bury the wooden post 6 ins. below the surface of the ground.
28.40	Intersect the Nevada-Utah State Line.