

410

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 70 E., MDM, NEVADA

CHAINS	
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd. T40N R70E S 32½ S 33 1987
43.00	Trail road, bears WNW. and ESE.
45.00	Ravine, drains W.
81.54	The cor. of secs. 28, 29, 32 and 33, monumented with a wooden post, 2 ins. square, 36 ins. long, firmly set in a mound of stone, with illegible scribe marks visible. At the corner point Set a stainless steel post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd. T40N R70E S 29 S 28 S 32 S 33 1987 Reset the original wooden post alongside the stainless steel post.
	S. 89° 50' E., bet. secs. 28 and 33. Over rolling land, through scattered sagebrush, greasewood and native grass.
39.52	Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T40N R70E S 28 ¼ S 33 1987
	Set a steel fence post, 5½ ft. long, alongside the stainless steel post.
61.00	Wash, 10 lks. wide, 1 ft. deep, drains N.
66.30	Power line, bears N. and S.
84.97	Intersect the Nevada-Utah State Line. Point for the closing cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.