

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 70 E., MDM, NEVADA

CHAINS	From this corner, a U.S.C. & G.S. Bench Mark, monumented with a standard brass tablet, set in the top of a 6 in. square concrete monument, exposed 4 ins. above ground, stamped "M 348 1953," bears N. 40° 18' E., 47.08 chs. dist. From this same corner, a U.S.C. & G.S. Bench Mark, monumented with a standard brass tablet, set in the top of a 6 in. square concrete monument, exposed 4 ins. above ground, stamped "L 348 1953," bears S. 73° 27' W., 37.33 chs. dist.	
	S. 88° 21' E., bet. secs. 21 and 28. Over rolling land, through scattered sagebrush, greasewood and native grass. 27.10 Trail road, bears NW. and SE. 37.40 Trail road, bears NNW. and SSE. 39.41 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T40N R70E S 21 $\frac{1}{4}$ S 28 1987 Set a steel fence post, 5½ ft. long, alongside the stainless steel post.	
57.50	Wash, 20 lks. wide, 2 ft. deep, drains NNW.	
66.10	Power line, bears N. and S.	
84.73	Intersect the Nevada-Utah State Line.	
	Point for the closing cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T40N S 21 CC S 28 R70E 1987 Set a steel fence post, 5½ ft. long, alongside the stainless steel post. From this corner, Mile Post No. 1, on the Nevada-Utah State Line, hereinbefore described, bears S. 0° 10' W., 4.57 chs. dist.	