

417

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 70 E., MDM, NEVADA

CHAINS 82.32 39.39 84.89	From this corner, a steel fence post, exposed 24 ins., bears N. 45° 22' E., 1.19 chs. dist. Point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd. T40N R70E S 5 S 4 S 8 S 9 1987 S. 87° 54' E., bet. secs. 4 and 9. Over rolling land, through scattered sagebrush, greasewood and native grass. Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T40N R70E S 4 ¼ S 9 1987 Set a steel fence post, 5½ ft. long, alongside the stainless steel post. Intersect the Nevada-Utah State Line. Point for the closing cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T40N CC S 4 S 9 R70E 1987 Set a steel fence post, 5½ ft. long, alongside the stainless steel post. From this corner, Mile Post No. 2, on the Nevada-Utah State Line, hereinbefore described, bears S. 0° 08' W., 6.03 chs. dist.
--	---