

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 70 E., MDM, NEVADA

CHAINS	
	T40N R70E $\frac{1}{4} \frac{S}{S} \frac{6}{7}$ 1987 Set a steel fence post, 5½ ft. long, alongside the stainless steel post. From this corner, a steel fence post, exposed 24 ins. above ground, bears N. 13° 31' E., 0.51 chs. dist. From this same corner, a U.S.G.S. Bench Mark, monumented with a standard brass tablet, set in the top of a 6 in. square concrete monument, exposed 6 ins. above ground, stamped "4809 FEET GWM 17 1939," bears S. 15° 19' E., 35.77 chs. dist.
69.20	Trail road, bears NNE. and SSW.
76.00	Trail road, bears NW. and SE.
83.98	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., firmly set and exposed 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy. of T. 40 N., R. 69 E., executed under Group No. 640. From the cor. of secs. 5, 6, 7 and 8. N. 3° 23' W., bet. secs. 5 and 6. Over gently rolling land, through scattered sagebrush and native grass.
15.00	Trail road, bears ENE. and WSW.
18.00	Wash, 20 lks. wide, 4 ft. deep, drains ESE.
30.00	Enter reseeded land, through crested wheatgrass.
41.28	Point for the ¼ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd. T40N R70E $\frac{1}{4} \frac{S}{S} \frac{6}{S} \frac{5}{5}$ 1987
79.56	Intersect the Eighth Standard Parallel North. Point for the closing cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.