

TOWNSHIP 16 NORTH, RANGE 19 EAST, MDM, NEVADA

CHAINS

The mean magnetic declination was found to be 16° E.

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 19 EAST,
T. 16 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
B. Ives, U.S. Deputy Surveyor,
in 1861

Beginning at the standard cor. of secs. 35 and 36, monumented with a galvanized iron pipe, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with galvanized iron cap mkd. as recorded in Washoe County, Record of Survey, No. 636, Subdivision Tract Map, No. 1542. This point is locally recognized as the corner and is accepted as the best available evidence of the position of the original corner.

Thorough search was made for the three original bearing trees - no evidence found. Considerable ground disturbance in area due to recent leveling and construction.

Remark the iron cap to read:

SC
T16N R19E
S 35|S 36
RE 235
BLM 1988

This monument meets the standards set by the Bureau of Land Management and was not remonumented.

from which

An underground phone cable terminal post, 6 ins. sq., projecting 28 ins. above ground, bears N. 64° 00' W., 97 lks. dist.

From this corner the standard cor. of Tps. 16 N., Rs. 19 and 20 E., bears S.89° 53.0" E., 80.131 chs. dist., monumented with a chiseled granite stone, 7X9 ins. sq., firmly set, projecting 12 ins. above ground, mkd. with - 6 grooves chiseled on E. side, 6 grooves chiseled on S. side, 6 grooves (4 plainly visible, 2 faint) chiseled on W. side, no visible marks on N. side, the marks SC plainly chiseled on flat top of stone, and brass disk mkd. RLS 3579 nailed to top center of stone.