

203

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 30 N., R. 56 E., MDM, NEVADA

CHAINS 40.15	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T30N R56E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{4}{9}$ 1987 Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.
49.90	Wash, 20 lks. wide, 2 ft. deep, drains NW.
59.60	Ravine, trail road in bottom, drains NNW.
80.30	The cor. of secs. 4, 5, 8 and 9.
	N. 0° 24' E., bet. secs. 4 and 5. Over rolling reseeded land, through scattered sagebrush, rabbit brush and crested wheat grass.
38.10	Trail road, bears E. and W.
39.94	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T30N R56E $\frac{1}{4}$ S 5 $\frac{1}{2}$ S 4 1987 Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.
40.50	Fence, bears E. and W.
56.90	Willow Creek, 10 lks. wide, 2 ft. deep, course NW.
69.20	Fence, bears E. and W.
82.71	Intersect the Sixth Standard Parallel North.
	The closing cor. of secs. 4 and 5, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 4 ins. above ground with brass cap mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North, through a portion of R. 56 E., executed under Group No. 506. Add the marks 1987 to the brass cap.