

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
TOWNSHIP 15 NORTH, RANGE 19 EAST, MDM, NEVADA

CHAINS

T15N
R18E R19E
S 12 $\frac{1}{4}$ S 7

1991

from which

A jeffrey pine, 14 ins. diam., bears N. 81°15' E., 94 lks. dist., mkd. $\frac{1}{4}$ S7 BT.

Cor. is located on mild W. slope in sandy area, 10 lks. E. of lake high water bank mark.

From the cor. of secs. 1, 6, 7, and 12, monumented with an iron pipe, 1½ ins. diam., projecting 14 ins. above an embedded collar of stone, 2 ft. diam., with iron hexagonal cap, as recorded in Washoe County, Record of Survey, # 1436, from which the original bearing trees

A red fir, 55 ins. diam., bears N. 27°15' E., 63 lks. dist., with healed breast and foot blazes - breast blaze previously hacked open - no marks visible due to hack marks (Record, N. 30° E.)

A red fir, 38 ins. diam., bears S. 39°00' E., 138 lks. dist., with healed breast and foot blazes. (Record, S. 40°15' E., 140 lks.)

A red fir, 28 ins. diam., bears S. 78°00' W., 107 lks. dist., with healed breast and foot blazes. (Record, S. 77°10' W., 103 lks.)

A red fir, 37 ins. diam., bears N. 40°30' W., 75 lks. dist., with healed breast and foot blazes - breast blaze previously hacked on. (Record, N. 39°30' W., 73 lks.)

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground overtop of pipe, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T15N
R18E R19E
S 1 S 6
S 12 S 7

1991

Cor. is located on moderate S. slope in area of boulders, red fir, and low brush.

From this cor. the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, bears S. 0°02'50" W., 39.875 chs. dist., heretofore described.

N. 0°08'00" E., bet. secs. 1 and 6.