

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 15 NORTH, RANGE 19 EAST, MDM, NEVADA

CHAINS			
	At the corner point Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground with a magnet at base, and in a mound of stone, 4 ft. base, to top, with brass cap mkd. T15N R19E S 3 $\frac{1}{4}$ S 10 1990 from which A jeffrey pine, 22 ins. diam., bears S. 31°00' W., 115 lks. dist., mkd. $\frac{1}{4}$ S10 BT. A jeffrey pine, 17 ins. diam., bears N. 43°45' W., 96 lks. dist., mkd. $\frac{1}{4}$ S3 BT. Cor. is located on a moderate E. slope in opening among trees on large spur, sloping E., in area of sandy soil, scattered brush, and moderately thick pine trees. S. 89°30'10" W., beginning new measurement.		
39.639	The cor. of secs. 3, 4, 9, and 10.		
	N. 0°24'50" W., bet. secs. 3 and 4.		
40.024	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate dist.; there is no evidence of the original cor. Not monumented.		
82.270	Intersect the Third Standard Parallel North. Point for the closing cor. of secs. 3 and 4, at proportionate dist.; there is no evidence of the original cor. Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground with a magnet at base, and in a mound of stone, 2$\frac{1}{2}$ ft. base, to top, with brass cap mkd. T16N R19E S 34 <table style="margin: 0 auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 4</td> <td style="padding: 0 5px;">S 3</td> </tr> </table> T15N R19E C C 1990	S 4	S 3
S 4	S 3		