

442

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 65 EAST, MDM, NEVADA

CHAINS 40.84	The standard $\frac{1}{4}$ sec. cor. of sec. 32, monumented with a redwood post, 3 ins. square, 36 ins. long, with illegible scribe marks visible, loosely set in a mound of earth. At the corner point Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. SC T41N R65E <u>$\frac{1}{4}$ S 32</u> 1989 Reset the original wooden post and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post. N. $88^{\circ} 37' W.$, beginning new measurement. Over rolling land.
40.44	The standard cor. of secs. 31 and 32, monumented with the decayed remains of a juniper post in pieces, with illegible scribe marks visible, loosely set alongside a redwood post, 3 ins. square, 36 ins. long, with illegible scribe marks visible, loosely set and exposed 30 ins. above ground. At the corner point Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. SC T41N R65E <u>S 31 S 32</u> 1989 Reset the original wooden post, the redwood post and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post. From this corner, U.S.G.S. Bench Mark, monumented with a standard brass tablet, firmly set in a concrete cylinder, 8 ins. diam., exposed 4 ins. above ground, with brass tablet mkd. 4-0 1967, bears S. $36^{\circ} 44' E.$, 36.90 chs. dist. N. $88^{\circ} 32' W.$, on the S. bdy. of sec. 31. Over rolling land, through scattered sagebrush and native grass.
13.40	Improved road, parallels power line.
14.70	Power line, bears N. $28\frac{1}{2}^{\circ} W.$ and S. $28\frac{1}{2}^{\circ} E.$