

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 22 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 2.70	Trail road, bears NNW. and SSE.
8.50	Top of spur, slopes N.
19.80	Bottom east side of Eldorado Canyon, bears irregularly NNE.
23.40	Bottom west side of Eldorado Canyon, bears irregularly NNE.
28.00	Trail road, bears NNW. and S.
40.006	The standard cor. of Tps. 16 N., Rs. 21 and 22 E., monumented with an iron post, 3 ins. diam., firmly set showing 10 ins. above the ground, with brass cap mkd. as described in the field notes of T. 16 N., R. 21 E., executed under Group No. 313.
DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY, T. 16 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA Reestablishment of the Survey Executed by U. S. Deputy Surveyor Butler Ives in 1865 From the standard cor. of Tps. 16 N., Rs. 21 and 22 E. N. 0°00'50" E., bet. secs. 31 and 36. Over rolling land, covered with medium sagebrush, rabbitbrush, native grasses, scattered pinon pine and juniper.	
13.80	Trail road, bears NW. and SE.
39.80	Fence, bears westerly and easterly 3.2 lks. dist. to corner of fences, bearing westerly and northerly.
40.104	The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with a wooden hub, 2 ins. square, 12 ins. long, firmly set in a mound of stone, with decayed remains of the original wood post with illegible scribing visible scattered in mound. At the corner point Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T16N R21E R22E 1/4 S36 S31 1995 Reset decayed remains of original wood post alongside the stainless steel post, insert the wooden hub inside the stainless steel post and rebuild the mound of stone, 3 ft. base, 3 ft. high, W. of cor.
	N. 0°02'00" E., beginning new measurement.