

247

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of a Portion of the Survey Executed by
S.W. Foreman, U.S. Deputy Surveyor, in 1865

From the cor. of secs. 11 and 14 only, monumented with a basalt stone, 20x9x7 ins. (1865 Record, 17x9x5 ins.; 1903 Record, 18x13x5 ins.), firmly set, plainly mkd. with 4 grooves on S. face and 1 groove on E. face (1903 Record, notches, edges), and a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T19N	R21E
S11	
S14	S12

2003

Deposit the original corner stone alongside the stainless steel post.

N. 0°03'20" E., bet. secs. 11 and 12.

Over rolling foothills, covered with scattered sagebrush and native grass.

40.299

The 1/4 sec. cor. of secs. 11 and 12, set by S.W. Foreman in 1865, under Contract K, monumented with a basalt stone, 20x10x6 ins. (1865 Record, 20x10x8 ins.), firmly set in a mound of stone, 3 ft. base, plainly mkd. with 1/4 on W. face, with an X on top.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T19N	R21E
1/4	
S11	S12

2003

Deposit the original corner stone alongside the stainless steel post.