

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Reestablishment of a Portion of the Survey Executed by E.A. Carter, U.S. Deputy Surveyor, in 1881, a Portion of the Dependent Resurvey Executed by R.C. Yundt, U.S. Surveyor and R.F. Wilson, U.S. Transitman, in 1933-34, and a Portion of the Dependent Resurvey Executed by H.G. Parker, Cadastral Surveyor, in 1963 Beginning at the cor. of Tps. 17 and 18 S., Rs. 50 and 51 E., monumented with an iron post, 2 1/2 ins. diam., firmly set on a rock ledge, in a mound of stone, 5 ft. diam., to top, with brass cap mkd. as described in the field notes of the dependent resurvey of the east boundary of T. 17 S., R. 50 E., executed under Group No. 408. N. 88°30'50" W., bet. secs. 1 and 36. Over nearly level land. 21.061 The E 1/16 sec. cor. of secs. 1 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the south boundary of T. 17 S., R. 50 E., executed under Group No. 408, with a wooden post, 4 ins. square, mkd. US BOUNDARY NPS, firmly set alongside. N. 88°30'00" W., beginning new measurement. 21.121 The 1/4 sec. cor. of secs. 1 and 36, monumented with an iron post, 2 1/2 ins. diam., cemented in a mound of stone, 5 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of the south boundary of T. 17 S., R. 50 E., executed under Group No. 408, with a wooden post, 4 ins. square, mkd. US BOUNDARY NPS, firmly set alongside. From the cor. of secs. 4, 5, 32 and 33, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., firmly set 10 ins. below the surface an improved gravel road, with a plastic cap not legible. This monument is locally recognized as the position of the original corner, is harmoniously related to other existing original and local corners and is accepted as the best available evidence of the position of the original corner. from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic- encased magnet, for a reference monument, bears N. 43°33' E., 70.3 lks. dist., with brass cap mkd. RM T17S R50E 46.4 FT TO COR S33 2007 and an arrow pointing to the corner. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic- encased magnet, for a reference monument, bears N. 43°27' W., 78.2 lks. dist., with brass cap mkd. RM T17S R50E 51.6 FT TO COR S32 2007 and an arrow pointing to the corner.
--------	--