

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. T18S R51E <table style="margin: auto;"> <tr> <td>S 5</td><td>S 4</td></tr> <tr> <td>S 8</td><td>S 9</td></tr> </table> 2007 Insert rebar inside stainless steel post. N. 0°58'30" W., bet. secs. 4 and 5. Over nearly level land, ascending gradually through scattered sagebrush. 41.596 Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T18S R51E 1/4 <table style="margin: auto;"> <tr> <td>S 5</td><td>S 4</td></tr> </table> 2007 62.394 The N 1/16 sec. cor. of secs. 4 and 5, determined by Richard L. Hafen, Nevada Professional Land Surveyor No. 4428, monumented with a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above the ground, with plastic cap mkd. RLS 4428, as recorded in Nye County, Nevada, Record of Survey, Document No. 17152 (Sheet 13). This is accepted as a careful and faithful determination of the position of the corner. N. 0°58'30" W., beginning new measurement. Ascend steep slope. 20.465 The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 5 ft. base, 3 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the S. bdy. of T. 17 S., R. 51 E., executed under Group No. 433. From the cor. of secs. 28, 29, 32 and 33. S. 87°45'50" W., bet. secs. 29 and 32. Over nearly level land, through scattered sagebrush.	S 5	S 4	S 8	S 9	S 5	S 4
S 5	S 4						
S 8	S 9						
S 5	S 4						