

DEPENDENT RESURVEY A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T16N R21E 1/4 S31 S32 2013 Insert rebar inside, and reset 1/2 in. steel pipe alongside stainless steel post. From this cor., the cor. of secs. 29, 30, 31 and 32, bears N. 0°06'40" E., 40.643 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the retracement of a portion of T. 16 N., R. 21 E., executed under Group No. 173. SUBDIVISION OF SECTION 31, T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA From the standard 1/4 sec. cor. of sec. 31, T. 16 N., R. 21 E., identical with the 1/4 sec. cor. of sec. 6, T. 15 N., R. 21 E. N. 0°10'40" W., on the N-S center line of sec. 31. Over rolling terrain, through scattered sagebrush. 9.57 Trail road, 15 lks. wide, bears E. and W. 13.593 The witness point at the intersection of Carson City and Lyon County Line with the N-S center line of sec. 31, hereinafter described. 20.216 The C-S 1/16 sec. cor. of sec. 31, determined by Walter G. Reid, Nevada Professional Land Surveyor No. 235, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 5 ins. above the ground, with tag wired to rebar, mkd. LS 235, as recorded in Lyon County, Nevada, Parcel Map, File No. 99713. This is accepted as a careful and faithful determination of the position of the corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. C S 1/16 S31 C 2013 Insert rebar inside stainless steel post.
--------	--